



VALVE SPRINGS

Part #	913	26123	26523	990	975	909	902	906		988	26113	26125	901	974	980	26981	981	983	Part #
# of Springs	Double	Beehive™	Beehive™	Single	Single	Single	Single	Single		Double	Beehive™	Beehive™	Single	Single	Single	Beehive™	Single	Single	# of Springs
Installed Height	1.475	1.470	1.470	1.500	1.500	1.550	1.600	1.600		1.600	1.640	1.640	1.650	1.650	1.700	1.700	1.700	1.700	Installed Height
O.D. of Outer	1.171	.943/1.105	.943/1.105	1.437	.953	1.159	1.355	1.355		1.384	0.959/1.061	1.013/1.101	1.494	.937	1.230	1.065/1.240	1.254	1.260	O.D. of Outer
I.D. of Outer	.875	.580/.742	.580/.742	1.073	.697	.837	1.000	1.011		1.060	.636/.738	0.650/0.738	1.080	.697	.876	.650/.825	.880	.836	I.D. of Outer
I.D. of Inner	.615	N/A	N/A	N/A	N/A	N/A	N/A	N/A		.804	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	I.D. of Inner
Spring Rate	296	324	324	269	144	240	280	219		230	191	258	353	96	308	347	370	410	Spring Rate
Damper	No	No	No	Yes	No	No	No	No		No	No	No	Yes	No	Yes	No	Yes	No	Damper
Spring Height (inches)	Spring Loads (Lbs.)									Spring Loads (Lbs.)									Spring Height (inches)
2.300																			2.300
2.250																			2.250
2.200																			2.200
2.150																			2.150
2.100																			2.100
2.050																			2.050
2.000																			2.000
1.950																			1.950
1.900																			1.900
1.850																			1.850
1.800																			1.800
1.750															77	93	87	85	1.750
1.700												104	83	22	92	110	105	105	1.700
1.650							34	50		105	78	117	101	27	107	127	123	126	1.650
1.600						63	48	61		117	88	130	119	32	123	145	142	146	1.600
1.550		64	64	100	48	75	62	72		128	97	143	136	37	138	162	160	167	1.550
1.500	23	80	80	113	55	87	76	82		140	107	156	154	41	153	179	178	187	1.500
1.450	38	96	96	127	62	99	90	93		151	116	169	172	46	169	197	197	208	1.450
1.400	53	113	113	140	69	111	104	104		163	126	182	189	51	184	214	215	228	1.400
1.350	67	129	129	154	77	123	118	115		174	135	194	207	56	200	231	233	249	1.350
1.300	82	145	145	167	84	135	132	126		186	145	207	225	61	215	249	252	269	1.300
1.250	97	161	161	181	91	147	146	137		197	154	220	242	65	230	266	273	290	1.250
1.200	112	177	177	194	98	159	160	148		209	164	233	260	70		283	294	310	1.200
1.150	127	194	194	207	105	171		158		220	174	246		75		301			1.150
1.100	141	210	210	221	113	183		169		232	183	259		80					1.100
1.050	156	226	226	234	120	195				243	193	272		85					1.050
1.000	171	242	242	248	127	207					202	285		89					1.000
0.950	186																		0.950
0.900	201																		0.900
0.850																			0.850
Maximum Coil Bind Height	0.858	0.900	0.900	0.950	0.950	0.917	1.125	1.054		1.000	0.952	0.970	1.100	0.920	1.150	1.115	1.150	1.150	Maximum Coil Bind Height
Ti. Ret. (Std. Weight)	760	798	798	730						730			730		728		728		Ti. Ret. (Std. Weight)
Ti. Ret. (Light Weight)											791 702	791 702				788			Ti. Ret. (Light Weight)
Steel Ret. (Std. Weight)		799	799	740 743 744						740 743 744	792 700	700	740 743 744		742 750	787 795	742 750	751	Steel Ret. (Std. Weight)
Steel Ret. (Light Weight)				1730						1730	1723	1723	1730		1750		1750		Steel Ret. (Light Weight)
Seat 0.570 Guide Dia.																4693			Seat 0.570 Guide Dia.
Seat 0.630 Guide Dia.																			Seat 0.630 Guide Dia.
Spring Cup (O.D. Locator)																			Spring Cup (O.D. Locator)
Shims				4754			4754	4754		4754			4754		4753	4753	4753		Shims

VALVE SPRINGS



VALVE SPRINGS

Part #	903	970	994	26995	995	942	916	973		941	985	982	920	26921	937	26915	26918	Part #
# of Springs	Single	Single	Double	Beehive™	Double	Single	Double	Single		Single	Double	Conical	Single	Double	Single Inner	Beehive™	Beehive™	# of Springs
Installed Height	1.700	1.700	1.700	1.700	1.700	1.700	1.700	1.750		1.750	1.750	1.750	1.750	1.770	1.800	1.800	1.800	Installed Height
O.D. of Outer	1.400	1.406	1.437	1.065/1.415	1.437	1.437	1.550	.970		1.255	1.430	1.250/1.454	1.509	1.300	1.015	1.055/1.290	1.075/1.310	O.D. of Outer
I.D. of Outer	1.015	1.020	1.073	.650/1.000	1.073	1.039	1.166	.700		.871	1.070	.866/1.070	1.125	.895	.731	.650/.885	.650/.885	I.D. of Outer
I.D. of Inner	N/A	N/A	.697	N/A	.697	N/A	.896	N/A		N/A	.700	n/a	n/a	.655	N/A	N/A	N/A	I.D. of Inner
Spring Rate	293	251	367	280	402	339	392	134		454	366	362	251	408	156	313	372	Spring Rate
Damper	No	No	Yes	No	Yes	Yes	No	No		Yes	Yes	No	Yes	No	No	No	No	Damper
Spring Height (inches)	Spring Loads (Lbs.)									Spring Loads (Lbs.)								Spring Height (inches)
2.300																		2.300
2.250																		2.250
2.200																		2.200
2.150																		2.150
2.100																		2.100
2.050																		2.050
2.000																		2.000
1.950																		1.950
1.900																		1.900
1.850															46	89	106	1.850
1.800								39		107	146	82	124	123	54	105	125	1.800
1.750	65	67	84	123	95	98	180	46		130	165	100	137	143	62	121	144	1.750
1.700	80	80	102	137	115	115	200	53		153	181	118	149	164	69	136	162	1.700
1.650	95	92	120	151	135	132	220	59		175	199	136	162	184	77	152	181	1.650
1.600	109	105	139	165	155	149	239	66		198	217	154	174	204	85	168	199	1.600
1.550	124	118	157	179	175	165	259	73		221	236	172	187	225	93	183	218	1.550
1.500	139	130	175	193	195	182	278	80		244	254	191	199	245	101	199	237	1.500
1.450	153	143	194	207	216	199	298	86		266	272	209	212	265	108	215	255	1.450
1.400	168	155	212	221	236	216	318	93		289	291	227	224	286	116	230	274	1.400
1.350	182	168	230	235	256	233	337	100		312	309	245	237	306	124	246	293	1.350
1.300	197	180	249	249	276	250	357	106		334	327	263	250	327	132	262	311	1.300
1.250	212	193	267	263	296	267	376	113		358	346	281	262	347	139	277	330	1.250
1.200	226		286	277	316	284	396	120		381	364	299		367	147	293	348	1.200
1.150			303	291	336		416	126		403				388	155		367	1.150
1.100			321	305	356		435	133						408				1.100
1.050			340	320			455	140										1.050
1.000							474											1.000
0.950							494											0.950
0.900																		0.900
0.850																		0.850
Maximum Coil Bind Height	1.125	1.203	1.065	1.060	1.020	1.125	0.900	1.095		1.100	1.150	1.135	1.175	1.040	1.100	1.100	1.100	Maximum Coil Bind Height
Ti. Ret. (Std. Weight)			730		730	730	731			728	730	730	732					Ti. Ret. (Std. Weight)
Ti. Ret. (Light Weight)				788			720						721	754		772 762 788	772 762 788	Ti. Ret. (Light Weight)
Steel Ret. (Std. Weight)			740	787 795	740	768 747	741			750	740	743 740	741			774 783 761 787	774 783 761 787	Steel Ret. (Std. Weight)
Steel Ret. (Light Weight)			1730	1787	1730	1730	1731			1750	1730	1730	1731	1754		1772 1787	1772 1787	Steel Ret. (Light Weight)
Seat 0.570 Guide Dia.				4696												4705	4705	Seat 0.570 Guide Dia.
Seat 0.630 Guide Dia.																		Seat 0.630 Guide Dia.
Spring Cup (O.D. Locator)							4700						4704	4695				Spring Cup (O.D. Locator)
Shims	4754		4754	4755	4754	4754	4757			4753	4754	4754	4755	4753		4753	4753	Shims

VALVE SPRINGS



VALVE SPRINGS

Part #	961	26986	986	987	984	26056	972	914		926	917	26112	26925	26926	910	978	977	Part #
# of Springs	Single	Beehive™	Double	Double	Single	Beehive™	Single	Double		Single	Double	Double	Double	Double	Single	Double	Double	# of Springs
Installed Height	1.800	1.800	1.800	1.800	1.800	1.800	1.800	1.800		1.800	1.800	1.800	1.810	1.835	1.850	1.850	1.850	Installed Height
O.D. of Outer	1.390	1.065/1.415	1.430	1.430	1.430	1.185/1.454	1.460	1.489		1.476	1.550	1.550	1.320	1.319	1.354	1.460	1.460	O.D. of Outer
I.D. of Outer	.990	.650/1.000	1.070	1.070	1.070	.731/1.000	1.060	1.105		1.062	1.136	1.136	.958	.920	.940	1.060	1.060	I.D. of Outer
I.D. of Inner	N/A	N/A	.697	.697	N/A	N/A	N/A	.819		N/A	.824	.742	.680	.654	N/A	.697	.700	I.D. of Inner
Spring Rate	313	280	322	370	231	400	308	367		415	566	519	400	505	415	403	441	Spring Rate
Damper	Yes	No	Yes	Yes	Yes	No	Yes	No		Yes	No	Yes	No	No	Yes	Yes	Yes	Damper
Spring Height (inches)	Spring Loads (Lbs.)									Spring Loads (Lbs.)								Spring Height (inches)
2.300																		2.300
2.250																		2.250
2.200																		2.200
2.150																		2.150
2.100																		2.100
2.050																		2.050
2.000																		2.000
1.950																		1.950
1.900						120									72	107	133	1.900
1.850	61	95	103	104	82	140	109	147		88	172	120	125	121	92	127	155	1.850
1.800	77	109	117	121	95	160	124	165		109	200	146	145	146	113	147	177	1.800
1.750	93	123	132	138	105	180	139	183		129	228	172	165	171	134	167	199	1.750
1.700	108	137	147	156	115	200	155	202		150	257	198	185	197	155	187	222	1.700
1.650	124	151	163	174	125	220	170	220		171	285	223	205	222	175	208	244	1.650
1.600	140	165	179	193	135	240	185	238		192	313	249	225	247	196	228	266	1.600
1.550	155	179	196	211	146	260	201	257		213	341	275	245	272	217	248	288	1.550
1.500	171	193	212	230	158	280	216	275		234	370	301	265	298	238	268	310	1.500
1.450	187	207	228	249	169	300	231	293		255	398	327	285	323	258	288	332	1.450
1.400	202	221	244	268	181	320	247	312		276	426	353	305	348	279	308	354	1.400
1.350	218	235	261	286	192	340	262	330		296	455	379	325	373	300	329	376	1.350
1.300	234	249	277	305	204	360	277	349		317	483	405	345	399		349	398	1.300
1.250		263	293	324	215	380	293	367		338	511	431	365	424		369	420	1.250
1.200		277	310	343	232	400		385		359	539	457	385	449				1.200
1.150		291				420		404			568	483	405	465				1.150
1.100		305									596	509						1.100
1.050																		1.050
1.000																		1.000
0.950																		0.950
0.900																		0.900
0.850																		0.850
Maximum Coil Bind Height	1.260	1.060	1.150	1.150	1.150	1.100	1.195	1.100		1.140	1.050	1.086	1.100	1.100	1.280	1.195	1.195	Maximum Coil Bind Height
Ti. Ret. (Std. Weight)			730	730	730	785	730	731		730	731	729				730	730	Ti. Ret. (Std. Weight)
Ti. Ret. (Light Weight)		788						720			720							Ti. Ret. (Light Weight)
Steel Ret. (Std. Weight)		787 795	740	740	740 743 744	703 705	740 743 744	741		740	741					740	740	Steel Ret. (Std. Weight)
Steel Ret. (Light Weight)		1787	1730	1730	1730		1730	1731		1730	1731		1777,1779	1777,1779		1730	1730	Steel Ret. (Light Weight)
Seat 0.570 Guide Dia.		4696				4696		4776			4785	4778	4695	4695				Seat 0.570 Guide Dia.
Seat 0.630 Guide Dia.						4697		4777				4780						Seat 0.630 Guide Dia.
Spring Cup (O.D. Locator)						4704	4704	4704		4704	4700					4704	4704	Spring Cup (O.D. Locator)
Shims		4755	4754	4754	4754	4757	4755	4755		4755	4757	4757	4753	4753		4755	4755	Shims

VALVE SPRINGS



VALVE SPRINGS

Part #	928	26120	950	940	924	925	911	954		929	953	936	938	930	999	26094	943	Part #
# of Springs	Double	Beehive™	Double	Single	Double	Double	Single	Double		Double	Double	Single	Double	Double	Double	Double	Double	# of Springs
Installed Height	1.850	1.900	1.900	1.900	1.900	1.900	1.900	1.900		1.900	1.900	1.900	1.900	1.900	1.900	1.900	1.900	Installed Height
O.D. of Outer	1.550	1.095/1.445	1.464	1.464	1.509	1.509	1.524	1.525		1.535	1.539	1.539	1.539	1.550	1.550	1.550	1.550	O.D. of Outer
I.D. of Outer	1.150	.650/1.000	1.080	1.080	1.125	1.125	1.110	1.111		1.135	1.137	1.125	1.125	1.150	1.114	1.136	1.136	I.D. of Outer
I.D. of Inner	.795	N/A	.724	N/A	.697	.697	N/A	.730		.754	.747	N/A	.731	.795	.724	.752	.812	I.D. of Inner
Spring Rate	354	370	332	241	347	395	373	483		437	474	325	480	354	633	449	551	Spring Rate
Damper	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Damper
Spring Height (inches)	Spring Loads (Lbs.)									Spring Loads (Lbs.)								Spring Height (inches)
2.300																		2.300
2.250																		2.250
2.200																		2.200
2.150																		2.150
2.100																		2.100
2.050																		2.050
2.000																		2.000
1.950			116	80	95	92	104	185		118	124	133	180	135	183	156	212	1.950
1.900	153	148	133	93	112	111	122	210		140	148	149	204	153	215	178	240	1.900
1.850	171	166	149	105	129	131	141	234		162	172	165	228	171	246	200	268	1.850
1.800	188	185	166	117	147	151	160	258		183	195	182	252	188	278	223	295	1.800
1.750	206	203	182	129	164	171	178	282		205	219	198	276	206	310	245	323	1.750
1.700	224	222	199	141	181	190	197	306		227	243	214	300	224	341	268	350	1.700
1.650	242	240	216	153	199	210	216	330		249	266	230	324	242	373	290	378	1.650
1.600	259	259	232	165	216	230	234	354		271	290	247	348	259	405	313	405	1.600
1.550	277	277	249	177	233	250	253	379		293	314	263	372	277	436	335	433	1.550
1.500	295	296	266	189	251	269	272	403		315	337	279	396	295	468	358	460	1.500
1.450	312	314	282	201	268	289	290	427		336	361	295	420	312	499	380	488	1.450
1.400	330	333	299	213	285	309	309	451		358	385	312	444	330	531	403	516	1.400
1.350	348	351	316	225	303	329	328	475		380	408	328	468	348	563	425	543	1.350
1.300	365	370	332	237	320	349	346	499		402	432	344	492	365	594	447	571	1.300
1.250	383	388	349	249	337	368	365	524		424	456	360	516	383	626	470	598	1.250
1.200					355	388		548		446	479				658	492	626	1.200
1.150											503				690			1.150
1.100															722			1.100
1.050																		1.050
1.000																		1.000
0.950																		0.950
0.900																		0.900
0.850																		0.850
Maximum Coil Bind Height	1.160	1.230	1.200	1.200	1.175	1.175	1.200	1.170		1.160	1.085	1.225	1.225	1.160	1.090	1.200	1.160	Maximum Coil Bind Height
Ti. Ret. (Std. Weight)	732		730	730	732	732	732	732		732	732	732	738	732	732	732	731	Ti. Ret. (Std. Weight)
Ti. Ret. (Light Weight)	721	794			721	721	721	721		721	721	721		721	721	721	720	Ti. Ret. (Light Weight)
Steel Ret. (Std. Weight)	741	795	740 743 744	740	741	741	741	741		741	741	741	741	741		749	749	Steel Ret. (Std. Weight)
Steel Ret. (Light Weight)	1732		1730	1730	1732	1732	1731	1732		1732	1732	1731	1732	1732	1732	1732	1731	Steel Ret. (Light Weight)
Seat 0.570 Guide Dia.	4776	4696	4781			4771	4779	4781		4772	4772		4778	4776	4781	4772	4785	Seat 0.570 Guide Dia.
Seat 0.630 Guide Dia.	4777	4697	4782		4770	4783		4782		4773	4773		4780	4777	4782	4773	4777	Seat 0.630 Guide Dia.
Spring Cup (O.D. Locator)	4700	4698	4704	4704	4700	4700		4700		4700	4700	4700	4700	4700	4700	4700		Spring Cup (O.D. Locator)
Shims	4757	4754	4755	4755	4757	4757	4757	4757		4757	4757	4757	4757	4757	4757	4757	4757	Shims

VALVE SPRINGS



VALVE SPRINGS

Part #	998	946	26055	912	939	927	919	933		935	944	951	991	26097	26089	955	932	Part #
# of Springs	Double	Triple	Beehive™	Single	Double	Double	Double	Double		Double	Double	Double	Double	Double	Double	Double	Double	# of Springs
Installed Height	1.900	1.900	1.925	1.950	1.950	1.950	1.950	1.950		1.950	1.950	1.950	1.950	2.000	2.000	2.000	2.000	Installed Height
O.D. of Outer	1.625	1.645	1.204/1.585	.896	1.539	1.539	1.540	1.550		1.554	1.570	1.620	1.639	1.539	1.550	1.550	1.557	O.D. of Outer
I.D. of Outer	1.175	1.195	.731/1.112	.600	1.125	1.125	1.126	1.136		1.140	1.120	1.170	1.190	1.125	1.136	1.136	1.143	I.D. of Outer
I.D. of Inner	.769	.871/.635	N/A	N/A	.697	.731	.814	.730		.746	.796	.846	.782	.731	.812	.812	.749	I.D. of Inner
Spring Rate	677	688	400	240	469	498	550	494		471	743	640	640	490	500	526	452	Spring Rate
Damper	Yes	No	No	No	Yes	Yes	No	Yes		Yes	No	No	Yes	Yes	No	No	Yes	Damper
Spring Height (inches)	Spring Loads (Lbs.)									Spring Loads (Lbs.)								Spring Height (inches)
2.300																		2.300
2.250																		2.250
2.200																		2.200
2.150																		2.150
2.100																		2.100
2.050														171	205	214	174	2.050
2.000			120	38	115	172	166	146		170	153	198	182	195	230	240	196	2.000
1.950	216	319	140	50	138	197	194	171		194	190	230	214	220	255	266	219	1.950
1.900	250	353	160	62	161	222	221	196		218	227	262	246	244	280	293	242	1.900
1.850	284	387	180	74	185	247	249	220		241	264	294	278	269	305	319	264	1.850
1.800	318	422	200	86	208	272	276	245		265	301	326	310	293	330	345	287	1.800
1.750	352	456	220	98	232	297	304	270		288	339	358	342	318	355	371	309	1.750
1.700	385	491	240	110	255	321	331	295		312	376	390	374	342	380	398	332	1.700
1.650	419	525	260	122	279	346	359	319		335	413	422	406	367	405	424	355	1.650
1.600	453	559	280	134	302	371	386	344		359	450	454	438	392	430	450	377	1.600
1.550	487	594	300	146	325	396	414	369		382	487	486	470	416	455	477	400	1.550
1.500	521	628	320	158	349	421	441	393		406	524	518	502	441	480	503	422	1.500
1.450	555	663	340	170	372	446	469	418		430	562	550	534	465	505	529	445	1.450
1.400	588	697	360	182	396	471	496	443		453	599	582	566	490	530	555	468	1.400
1.350	622	732	380		419	496	524	467		477	636	614	598	514	555	582	490	1.350
1.300	656	766	400		443	520	551	492		500	673	646	630	539	580	608	513	1.300
1.250	690	800	420		466	545	579	517		524	710	678	662	563			535	1.250
1.200	724	835					606				747	710	694	597			558	1.200
1.150	758	869					634				784	742					581	1.150
1.100																		1.100
1.050																		1.050
1.000																		1.000
0.950																		0.950
0.900																		0.900
0.850																		0.850
Maximum Coil Bind Height	1.090	1.130	1.225	1.360	1.225	1.175	1.100	1.200		1.180	1.100	1.100	1.125	1.135	1.230	1.230	1.160	Maximum Coil Bind Height
Ti. Ret. (Std. Weight)	733	739 735		753	732	732	731	732		724	731	736	733	732	731	731	738	Ti. Ret. (Std. Weight)
Ti. Ret. (Light Weight)		722	785		721	721	720	721			720			721	720	720		Ti. Ret. (Light Weight)
Steel Ret. (Std. Weight)			703 705		741		741	741		748						749	748	Steel Ret. (Std. Weight)
Steel Ret. (Light Weight)						1732	1731	1732		1732	1732			1731	1731	1731	1732	Steel Ret. (Light Weight)
Seat 0.570 Guide Dia.	4774		4696		4770 4771	4778	4785	4781		4772	4776		4774	4778	4785	4785	4772	Seat 0.570 Guide Dia.
Seat 0.630 Guide Dia.	4775		4697		4783	4780		4782		4773	4777		4775	4780	4777	4777	4773	Seat 0.630 Guide Dia.
Spring Cup (O.D. Locator)	4702	4702	4702 4711		4700	4700	4700	4700		4700	4702	4702	4702	4700	4700	4700	4700	Spring Cup (O.D. Locator)
Shims	4756	4756	4757		4757	4757	4757	4757		4757	4757	4756	4756	4757	4757	4757	4757	Shims

VALVE SPRINGS

Part #	26095	996	959	26115	26099	947	948	26082	26028
# of Springs	Single	Double	Double	Double	Double	Triple	Triple	Triple	Triple
Installed Height	2.000	2.000	2.000	2.050	2.050	2.050	2.100	2.100	2.200
O.D. of Outer	1.185/1.589	1.625	1.645	1.549	1.625	1.645	1.645	1.680	1.677
I.D. of Outer	.731/1.135	1.175	1.195	1.125	1.175	1.195	1.195	1.195	1.195
I.D. of Inner	N/A	.769	.871	.719	.769	.871/.635	.871/.635	.871/.635	.872/.635
Spring Rate	300	637	580	544	561	681	686	761	728
Damper	No	Yes	No	Yes	Yes	No	No	No	No
Spring Height (inches)	Spring Loads (Lbs.)								
2.300									
2.250									310
2.200									346
2.150							298	344	382
2.100				201	217	270	332	382	419
2.050	135	243	207	228	245	304	366	420	455
2.000	150	275	236	255	273	338	401	458	492
1.950	165	307	265	283	301	372	435	496	528
1.900	180	338	294	310	329	406	469	534	564
1.850	195	370	323	337	357	440	504	572	601
1.800	210	402	352	364	385	474	538	610	637
1.750	225	434	381	391	413	508	572	648	674
1.700	240	466	410	418	441	542	606	686	710
1.650	255	498	439	446	469	576	641	724	746
1.600	270	529	468	473	497	610	675	763	783
1.550	285	561	497	500	525	644	709	801	819
1.500	300	593	526	527	553	678	744	839	856
1.450	315	625	555	554	581	712	778	877	892
1.400	330	657	584	582	609	746	812	915	928
1.350	345	689	613	609	637	781	847	953	965
1.300	360	721	642	636	665	815	881	991	1001
1.250	375	752	671	663	693	849	915	1029	1038
1.200	390	784	700			883	949	1067	1074
1.150	405	816	729			917		1105	
1.100									
1.050									
1.000									
0.950									
0.900									
0.850									
Maximum Coil Bind Height	1.130	1.100	1.130	1.192	1.184	1.145	1.130	1.130	1.142
Ti. Ret. (Std. Weight)		733	739	732	733	739 735	739 735	739 735	739 735
Ti. Ret. (Light Weight)	785					722	722	722	722
Steel Ret. (Std. Weight)	703 705			748					
Steel Ret. (Light Weight)				1731					
Seat 0.570 Guide Dia.	4711	4774		4781	4774				
Seat 0.630 Guide Dia.		4775		4782	4775				
Spring Cup (O.D. Locator)	4702	4702	4702	4700	4702	4702	4702	4708	4708
Shims	4757	4756	4756	4757	4757	4756	4756	4756	4756