

<u>Year</u>	<u>Axle</u>	<u>Body</u>	<u>(F)</u>	<u>(P)</u>	<u>(C)</u>	<u>(D)</u>	<u>(T)</u>	<u>(W)</u>	
1972	7 1/4"	B		47.30"	10.09"		61.60"	5x4.5"	Suspected to be 57.625" flange to flange or F = 57.80"
1971-81	8 1/4"	BR	57.625"	47.30"	11.69"		62.00"	5x4.5"	
1971-81	9 1/4"	BR	57.625"	47.30"	11.69"		62.00"	5x4.5"	
1971-74	8 3/4"	B	57.734"	47.30"	12.35"	63.00"	62.00"	5x4.5"	
1971-72	9 3/4"	B	57.875"	47.30"	13.47"	60.13"	62.00"	5x4.5"	
1975-78	8 1/4"	C	59.200"	47.30"	11.69"		63.40"	5x4.5"	Suspected to be 59.20" flange to flange
1971-78	9 1/4"	B SW		47.30"	11.69"		63.40"	5x4.5"	
1975-78	9 1/4"	B SW & C (all)	59.200"	47.30"	11.69"		63.40"	5x4.5"	
1971-74	8 3/4"	B SW	59.437"	47.30"	12.35"	64.38"	63.40"	5x4.5"	
1964	8 1/4"	B	55.625"	44.00"	12.35"	60.88"	59.60"	5x4.5"	Except Max Wedge
1969	8 3/4"	C	56.437"	46.00"	12.35"	61.75"	60.20"	5x4.5"	
1969	8 3/4"	C SW	56.437"	46.00"	12.35"		62.40"	5x4.5"	
1970-74	8 3/4"	E	56.437"	46.00"	12.35"	61.63"	60.70"	5x4.5"	Same as 65-68 C
1965-68	8 3/4"	C	56.750"	46.00"	12.35"	61.75"	60.70"	5x4.5"	
1964-70	8 3/4"	A100	56.750"	46.00"	12.35"	61.75"	61.75"		
1965-66	8 3/4"	Y	57.00"	46.00"	12.35"	61.94"	61.70"	5x5.5"	
1967-69	8 3/4"	Y	57.375"	46.00"	12.35"	62.31"	61.10"		Chrysler/Fury only Top mounted Perches! Top mounted Perches! & '69 C SW?
1970-71	8 3/4"	C	57.875"	46.00"	12.35"	63.00"	60.70"	5x4.5"	
1965-71	8 3/4"	D100	58.312"	43.25"	12.35"	63.94"	63.94"		
1972-74	8 3/4"	D100	59.437"	43.50" ?	12.35"	64.38"	64.38"		
1970-74	8 3/4"	C	59.437"	46.00"	12.35"	64.38"	62.00"	5x4.5"	
1972-73	8 3/4"	Y	59.437"	46.00"	12.35"	64.56"	63.40"		
1970-74	9 3/4"	E	56.437"	46.00"	13.47"	61.63"	60.70"	5x4.5"	

Column Names

(F) is Flange to Flange
 (P) is Perch Center to Perch Center
 (C) is Axle center to U-Joint center
 (D) is Drum to Drum (Wheel Mounting Surface)
 (T) is Tread (center of Tire to Tire)
 (W) is Wheel bolt pattern

Green and blank means "data not known"

Size/Color codes

7 1/4"

8 1/4"

8 3/4" (no color)

9 1/4"

9 3/4" (D60)